



LMU-2000™ GPRS/CDMA/HSPA Series

GPS Tracking Unit with OBD-II Connector



EXPERIENCE THE ADVANTAGE

- GSM/GPRS/CDMA 1xRTT or HSPA Configuration
- Superior GPS & cellular performance
- Built-in battery backup
- Built-in cellular and GPS antenna for easy installation
- Built-in OBD-II connector for easy installation
- Built-in Accelerometer for driver behavior monitoring and impact detection
- Pre-impact data capture capabilities
- Power sleep modes

The LMU-2000 is an economical, full-featured vehicle tracking product designed for easy and reliable installation in automobiles. The LMU-2000 is an ideal solution for automotive insurance, driver behavior management, auto rental, and easy-install fleet management and automotive applications.

COMPETITIVE PRICE, COMPETITIVE TECHNOLOGY, COMPETITIVE EDGE

The LMU-2000 full featured tracking unit from CalAmp features a small size, superior GPS design, OBD-II interface, and a 3-axis accelerometer. These features enable the LMU-2000 to track vehicle speed and location, detect hard braking, cornering or acceleration in addition to a full set of fleet management features. Superior internal antennas for both cellular and GPS coupled with an OBD-II connector eliminate the need for professional installation and makes the LMU-2000 install quick, easy and inexpensive. Messages are transported across the cellular network using enhanced SMS or UDP messaging providing a reliable communications link between the device and your application servers. The LMU-2000 is designed to dramatically reduce cost of ownership, power and size while providing excellent field reliability.

FLEXIBILITY

The LMU-2000 employs CalAmp's advanced industry leading on-board alert engine, PEG™ (Programmable Event Generator) to monitor external conditions and support customer-defined exception-based rules to meet your application requirements. PEG monitors the vehicle environment and responds instantaneously to pre-defined threshold conditions related to time, date, motion, location, geo-zone, input and other event combinations. This behavior can be programmed by CalAmp before shipment, at a customer's facility, or over-the-air once the unit has been fielded.

OVER-THE-AIR SERVICEABILITY

The LMU-2000 leverages CalAmp's management and maintenance system, PULS™ (Programming, Updates, and Logistics System), for over-the-air configuration parameters, PEG rules, and firmware. This out-of-the-box hands free configuration and automatic post-installation upgrades can monitor unit health status across your customers' fleets to identify issues before they become expensive problems.

LMU-2000 SPECIFICATIONS

GENERAL

Communication Modes	GPRS/EDGE/HSPA and CDMA 1xRTT Packet data, UDP and SMS
Location Technology	50 channel GPS
Operating Voltage	12 volt vehicle systems

GPS

Location Technology	50 channel GPS (with SBAS) SBAS: WAAS, EGNOS, MSAS, GAGAN
Location Accuracy	2.0 meter CEP (with SBAS)
Tracking Sensitivity	-162dBm
Acquisition Sensitivity	-147dBm
AGPS Capable	

CELLULAR

Data Support	SMS, GPRS, CDMA 1xRTT or HSPA packet data	
Operating Bands (MHz)		
GSM/GPRS	850/900/1800/1900	
CDMA/1XRTT	850/1800	
HSPA/UMTS	800(VI)/850(V)/900(VIII)/ 1700(IV)/1900(II)/2100(I)	
Transmitter Power		
GSM/GPRS	850/900	32.5 dBm
	1800/1900	29.3 dBm
CDMA/1XRTT	850	24 dBm
	1800	23 dBm
HSPA/UMTS	(all bands)	23 dBm
HSPA data rates	5.6 Mbps upload/7.2 Mbps download	
HSPA fallback	EDGE/GPRS/GSM quad band EDGE MCS1-MCS9 3GPP Release 6	

COMPREHENSIVE I/O

Inputs	OBD-II connector with ignition sense
Outputs	None
Serial Interface	1TTL serial
Status LEDs	GPS, OBD-II and cellular

ENVIRONMENTAL

Temperature	-30° to +75° C (operating) -40° to +85° C (storage)
Humidity	95%RH @ 50° C non-condensing
Shock and Vibration	SAE J1455
EMC/EMI	SAE J1113; FCC-Part 15B; Industry Canada
RoHS Compliant	

About CalAmp

CalAmp Corp. (NASDAQ: CAMP) is a proven leader in providing wireless communications solutions to a broad array of vertical market applications and customers. CalAmp's extensive portfolio of intelligent communications devices, robust and scalable cloud service platform, and targeted software applications streamline otherwise complex machine-to-machine (M2M) deployments. These solutions enable customers to optimize their operations by collecting, monitoring and efficiently reporting business critical data and desired intelligence from high-value remote assets. For more information, please visit www.calamp.com.

ELECTRICAL

Operating Voltage	7-20 VDC
Power Consumption	3 mA @ 12V (deep sleep) 11 mA @ 12V (sleep on network) 140 mA @ 12V (active)

PHYSICAL

Dimensions	1.7 x 2.5 x 1" , (43 x 64 x 25 mm)
Weight	1.8 oz, (51 g)

CONNECTORS, SIM ACCESS

SIM Access	Internal
Connection Type	Built-in OBD-II interface

CERTIFICATIONS

Fully certified FCC, CE, IC, PTCRB, Applicable Carriers

MOUNTING

Built-in OBD-II connector

KEY FEATURES

- OBD-II plug for power and ground with ignition sense
- Packet data (GPRS, CDMA 1xRTT, or HSPA) and SMS-based messaging
- Internal 200 mAh back-up battery
- Internal cellular and GPS antennas
- Super sensitive GPS (-162 dBm tracking)
- Ultra-low power sleep mode (<3mA)
- 3-axis accelerometer for driver behavior and impact detection
- Voltage monitoring and low battery notification
- 20,000 buffered messages
- 32 built-in geo-fences, plus any combination of circle or polygon zones, up to 5400 points
- PEG™ Exception-Based Rules
- Automatic, Over-The-Air Unit Configuration on Power-up (PULS™)
- Over-The-Air Firmware Download (PULS™)
- Web-Based Device Management (PULS™)
- Garmin® FMI compatible interface

OPTIONAL FEATURES/FUNCTIONS

- Serial cable
- Garmin® interface or MDT serial interface

DEVELOPMENT SUPPORT OPTIONS

Customized hardware and software development available on request

CalAmp Corp.

1401 N. Rice Avenue, Oxnard, CA 93030
T: 760.438.9010 | F: 760.438.5835
www.calamp.com

© 2013 CalAmp. PN: 000-0006-200 Rev 2

All specifications are typical and subject to change without notice

